Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Fray Check 22,5 ml Art.: 968020

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

See definition of the substance or mixture. Sector of use [SU]: SU21 - Consumer uses: Private households (=general public = consumers) Chemical product category [PC]: PC34 - Textile dyes, and impregnating products Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

PRYM CONSUMER Europe GmbH Zweifaller Str. 130 52224 Stolberg Deutschland Tel.: +49 (0)2402 - 14 04 Fax: +49 (0)2402 - 14 29 19

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:


Telephone number of the company in case of emergencies: +49 (0)2402 - 14 04

SECTION 2: Hazards identification

2.1 Classification of the substance or mixtureClassification according to Regulation (EC) 1272/2008 (CLP)Hazard classHazard categoryHazard statementFlam. Liq.3H226-Flammable liquid and vapour.Eye Dam.1H318-Causes serious eye damage.STOT SE3H336-May cause drowsiness or dizziness.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)





H226-Flammable liquid and vapour. H318-Causes serious eye damage. H336-May cause drowsiness or dizziness.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280-Wear eye protection.

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor.

P403+P233-Store in a well-ventilated place. Keep container tightly closed.

P501-Dispose of contents / container to an approved waste disposal facility.

Propan-1-ol

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. 3.2 Mixtures

J.2 MIA(0)05	
Propan-1-ol	
Registration number (REACH)	
Index	603-003-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	200-746-9
CAS	71-23-8
content %	80-<100
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Flam. Liq. 2, H225
factors	Eye Dam. 1, H318
	STOT SE 3, H336

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Page 3 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.03.2021 / 0006 Replacing version dated / version: 28.02.2019 / 0005 Valid from: 22.03.2021 PDF print date: 21.05.2021 Fray Check 22,5 ml Art.: 968020

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses. Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available. Protect uninjured eye. Follow-up examination by an ophthalmologist.

Ingestion

Rinse the mouth thoroughly with water.

Give copious water to drink - consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. The following may occur: Drying of the skin. Dermatitis (skin inflammation) If solvent components are inhaled above the air threshold-value: Headaches Dizziness Effect on the central nervous system Coordination disorders Mental confusion Narcotic effect. Ingestion: Nausea Vomiting Effects/damages the central nervous system In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray / alcohol resistant foam / CO2 / dry extinguisher.

Unsuitable extinguishing media

None known

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon

Toxic gases Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air. Remove possible causes of ignition - do not smoke. Avoid contact with eyes or skin. If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up. Resolve leaks if this possible without risk. Prevent surface and ground-water infiltration, as well as ground penetration. Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Keep away from sources of ignition - Do not smoke.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Do not store with flammable or self-igniting materials.

Observe special storage conditions.

Protect from direct sunlight and warming.

Store in a well ventilated place.

Store cool.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Propan-1-ol	Content %:80- <100
WEL-TWA: 200 ppm (500 mg/m	3) WEL-STEL: 250 ppm (625 mg/m3)	
Monitoring procedures:	- NIOSH 1401 (ALCOHOLS II) - 1994	
	- NIOSH 1405 (ALCOHOLS COMBINED) - 2003	
	 Draeger - Alcohol 100/a (CH 29 701) 	
BMGV:	Other information: Sk	

Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
	Environment - freshwater		PNEC	10	mg/l	
	Environment - marine		PNEC	1	mg/l	
	Environment - sediment, freshwater		PNEC	22,8	mg/kg	
	Environment - sediment, marine		PNEC	2,28	mg/kg	
	Environment - soil		PNEC	2,2	mg/kg	
	Environment - sewage treatment plant		PNEC	96	mg/l	

	Environment - sporadic (intermittent) release		PNEC	10	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	81	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	80	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	61	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	1036	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	136	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	268	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	1723	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and nonmetrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN 374). Recommended Protective gloves in butyl rubber (EN 374). With short-term contact: Protective gloves made of chloroprene (EN 374). Protective nitrile gloves (EN 374). Permeation time (penetration time) in minutes: max. 15 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended. Page 6 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.03.2021 / 0006 Replacing version dated / version: 28.02.2019 / 0005 Valid from: 22.03.2021 PDF print date: 21.05.2021 Fray Check 22,5 ml Art.: 968020

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. If OES or MEL is exceeded. Gas mask filter A (EN 14387), code colour brown Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

GB

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

5.1 mornation on basic physical and chemical p	operaes
Physical state:	Liquid
Colour:	According to specification
Odour:	Mild
Odour threshold:	Not determined
pH-value:	Mixture is non-soluble (in water).
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	23 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	2,1 Vol-%
Upper explosive limit:	13,5 Vol-%
Vapour pressure:	19 hPa
Vapour density (air = 1):	Not determined
Density:	Not determined
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	360 °C (Ignition temperature)
Decomposition temperature:	Not determined
Viscosity:	60 s (20°C, DIN 53211 (4 mm))
Explosive properties:	Product is not explosive. Possible build up of explosive/highly
	flammable vapour/air mixture.
Oxidising properties:	No
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	89,9 % (Organic solvents)

SECTION 10: Stability and reactivity

10.1 ReactivityThe product has not been tested.10.2 Chemical stability

Page 7 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.03.2021 / 0006 Replacing version dated / version: 28.02.2019 / 0005 Valid from: 22.03.2021 PDF print date: 21.05.2021 Fray Check 22,5 ml Art.: 968020

Stable with proper storage and handling. **10.3 Possibility of hazardous reactions**No dangerous reactions are known. **10.4 Conditions to avoid**See also section 7.
Heating, open flame, ignition sources **10.5 Incompatible materials**See also section 7.
Avoid contact with strong oxidizing agents. **10.6 Hazardous decomposition products**See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	-					n.d.a.
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-						
RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	8000	mg/kg	Rat	OECD 401 (Acute	
			0.0		Oral Toxicity)	
Acute toxicity, by dermal	LD50	4032	mg/kg	Rabbit	OECD 402 (Acute	
route:					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	> 33,8	mg/l	Rat	OECD 403 (Acute	
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Eye Dam. 1
damage/irritation:					Eye	
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation	
					Test)	
Carcinogenicity:						Negative
Aspiration hazard:						No

Page 8 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.03.2021 / 0006 Replacing version dated / version: 28.02.2019 / 0005 Valid from: 22.03.2021 PDF print date: 21.05.2021 Fray Check 22,5 ml

		• •
Symptoms:		respiratory
		distress,
		drowsiness,
		unconsciousnes
		s, coughing,
		headaches,
		intoxication,
		drowsiness,
		mucous
		membrane
		irritation,
		dizziness,
		nausea and
		vomiting.

SECTION 12: Ecological information

Fray Check 22,5 ml									
Art.: 968020									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
12.1. Toxicity to fish:							n.d.a.		
12.1. Toxicity to							n.d.a.		
daphnia:									
12.1. Toxicity to algae:							n.d.a.		
12.2. Persistence and							n.d.a.		
degradability:									
12.3. Bioaccumulative							n.d.a.		
potential:									
12.4. Mobility in soil:							n.d.a.		
12.5. Results of PBT							n.d.a.		
and vPvB assessment									
12.6. Other adverse							n.d.a.		
effects:									

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Other information:	H (Henry)		0,177				
12.1. Toxicity to fish:	LC50	96h	4555	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	3644	mg/l	Daphnia magna	DIN 38412 T.11	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>100	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion
12.1. Toxicity to algae:	NOEC/NOEL	48h	1150	mg/l	Selenastrum capricornutum	·	
12.1. Toxicity to algae:	EC50	48h	9170	mg/l	Pseudokirchnerie Ila subcapitata		
12.2. Persistence and degradability:		20d	75	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	83-92	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		0,2-0,34				Bioaccumulation n is unlikely (LogPow < 1).

12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to bacteria:	EC50	3h	>1000	mg/l	Pseudomonas putida	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	References
Other information:	AOX		0	%			Does not contain any organically bound halogens whic can contribute to the AOX value in waste water.DIN EN 1482
Other information:	Log Koc		0,633				

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

Do not perforate, cut up or weld uncleaned container.

Residues may present a risk of explosion.

SECTION 14: Transport information

General statements

14.3. Transport hazard class(es):

14.1. UN number:

14.4. Packing group:

Transport by road/by rail (ADR/RID), 14.2. UN proper shipping name:

UN 1993 FLAMMABLE LIQUID, N.O.S. (N-PROPANOL)

1993

3

Ш





Page 10 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.03.2021 / 0006 Replacing version dated / version: 28.02.2019 / 0005 Valid from: 22.03.2021 PDF print date: 21.05.2021 Fray Check 22,5 ml Art.: 968020 Classification code: F1 LQ: 5 L 14.5. Environmental hazards: Not applicable Tunnel restriction code: D/E Transport by sea (IMDG-code) 14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (N-PROPANOL) 3 14.3. Transport hazard class(es): 14.4. Packing group: Ш EmS: F-E, S-E Marine Pollutant: n.a 14.5. Environmental hazards: Not applicable Transport by air (IATA) 14.2. UN proper shipping name: Flammable liquid, n.o.s. (N-PROPANOL) 14.3. Transport hazard class(es): 3 14.4. Packing group: Ш 14.5. Environmental hazards: Not applicable 14.6. Special precautions for user Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations. Precautions must be taken to prevent damage. 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code Freighted as packaged goods rather than in bulk, therefore not applicable. Minimum amount regulations have not been taken into account. Danger code and packing code on request. Comply with special provisions. **SECTION 15: Regulatory information** 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
-		dangerous substances as	dangerous substances as
		referred to in Article 3(10) for	referred to in Article 3(10) for
		the application of - Lower-tier	the application of - Upper-tier
		requirements	requirements
P5c		5000	50000

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

89,9 %

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

1, 2, 8, 9, 11, 12, 14, 15

Employee training in handling dangerous goods is required. These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

7.11. 500020				
Classification in accordance with regulation	Evaluation method used			
(EC) No. 1272/2008 (CLP)				
Flam. Liq. 3, H226	Classification based on test data.			
Eye Dam. 1, H318	Classification according to calculation procedure.			
STOT SE 3, H336	Classification according to calculation procedure.			
The following phrases represent the posted Hazard Class and R (specified in Section 2 and 3). H225 Highly flammable liquid and vapour. H318 Causes serious eye damage. H336 May cause drowsiness or dizziness. Flam. Liq. — Flammable liquid Eye Dam. — Serious eye damage STOT SE — Specific target organ toxicity - single exposure - na	Risk Category Code (GHS/CLP) of the product and the constituents			
Any abbreviations and acronyms used in this document:				
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= F BSEF The International Bromine Council bw body weight CAS Chemical Abstracts Service CLP Classification, Labelling and Packaging (REGULATION (substances and mixtures) CMR CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level dw dry weight	Iaterials) ral Institute for Materials Research and Testing, Germany) rederal Institute for Occupational Health and Safety, Germany) (EC) No 1272/2008 on classification, labelling and packaging of			
e.g. for example (abbreviation of Latin 'exempli gratia'), for ins EC European Community				

- EN European Norms
- EPA United States Environmental Protection Agency (United States of America)
- etc. et cetera
- EU European Union
- EVAL Ethylene-vinyl alcohol copolymer
- Fax. Fax number
- gen. general
- GHS Globally Harmonized System of Classification and Labelling of Chemicals
- GWP Global warming potential
- IARC International Agency for Research on Cancer
- IATA International Air Transport Association
- IBC (Code) International Bulk Chemical (Code)
- IMDG-code International Maritime Code for Dangerous Goods
- incl. including, inclusive
- IUCLIDInternational Uniform Chemical Information Database
- IUPAC International Union for Pure Applied Chemistry
- LC50 Lethal Concentration to 50 % of a test population
- LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
- LQ Limited Quantities

Page 12 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.03.2021 / 0006 Replacing version dated / version: 28.02.2019 / 0005 Valid from: 22.03.2021 PDF print date: 21.05.2021 Fray Check 22,5 ml Art.: 968020 MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. n.av. not available not checked n.c. n.d.a. no data available OECD Organisation for Economic Co-operation and Development organic org. PBT persistent, bioaccumulative and toxic

ppm parts per million PVC Polyvinylchloride

PNEC Predicted No Effect Concentration

Polyethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

ΡE

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.